

Serial terminal started  
nRF24L01+ driver started  
Press any key to begin receiving  
Receive mode - 2402MHz  
Listening for traffic on node address \$E7E7E7E7E7

RSSI: -64  
Packets received: 3Received packet on pipe 0 from node \$E7 00000: E7% .  
54' T 45( E 53) S 54\* T 30+ 0 30, 0 30- 0" 30.  
0RSSI: -64  
Packets received: 3Received packet on pipe 0 from node \$E7 00000: E7% .  
54' T 45( E 53) S 54\* T 30+ 0 30, 0 30- 0" 31.  
1RSSI: -64  
Packets received: 3Received packet on pipe 0 from node \$E7 00000: E7% .  
54' T 45( E 53) S 54\* T 30+ 0 30, 0 30- 0" 32.  
2RSSI: -64  
Packets received: 3Received packet on pipe 0 from node \$E7 00000: E7% .  
54' T 45( E 53) S 54\* T 30+ 0 30, 0 30- 0" 33.  
3RSSI: -64  
Packets received: 3Received packet on pipe 0 from node \$E7 00000: E7% .  
54' T 45( E 53) S 54\* T 30+ 0 30, 0 30- 0" 34.  
4RSSI: -64  
Packets received: 3Received packet on pipe 0 from node \$E7 00000: E7% .  
54' T 45( E 53) S 54\* T 30+ 0 30, 0 30- 0" 35.  
5RSSI: -64  
Packets received: 3Received packet on pipe 0 from node \$E7 00000: E7% .  
54' T 45( E 53) S 54\* T 30+ 0 30, 0 30- 0" 36.  
6RSSI: -64  
Packets received: 3Received packet on pipe 0 from node \$E7 00000: E7% .  
54' T 45( E 53) S 54\* T 30+ 0 30, 0 30- 0" 37.  
7RSSI: -64  
Packets received: 4Received packet on pipe 0 from node \$E7 00000: E7% .  
54' T 45( E 53) S 54\* T 30+ 0 30, 0 30- 0" 38.  
8RSSI: -64  
Packets received: 4Received packet on pipe 0 from node \$E7 00000: E7% .  
54' T 45( E 53) S 54\* T 30+ 0 30, 0 30- 0" 39.  
9RSSI: -64  
Packets received: 4Received packet on pipe 0 from node \$E7 00000: E7% .  
54' T 45( E 53) S 54\* T 30+ 0 30, 0 31- 1" 30.  
0RSSI: -64  
Packets received: 4Received packet on pipe 0 from node \$E7 00000: E7% .  
54' T 45( E 53) S 54\* T 30+ 0 30, 0 31- 1" 31.  
1RSSI: -64  
Packets received: 4Received packet on pipe 0 from node \$E7 00000: E7% .  
54' T 45( E 53) S 54\* T 30+ 0 30, 0 31- 1" 32.

