


RoHS



X	2.54*POSITION NO.
Y	2.54*(POSITION NO.-1)



SPECIFICATIONS

Material

Insulator: Nylon 6T, glass reinforced, rated UL 94V-0
Contact: Phosphor Bronze or Brass

Electrical

Current Rating: 2 Amp
Contact Resistance: 30 mΩ max.
Insulation Resistance: 3000 MΩ min.
Dielectric Withstanding Voltage: 500V AC for 1 minute
Operating Temperature: -40°C to +105°C



5

HOW TO ORDER:

1. NO. OF CONTACT	2. CONTACT MATERIAL	3. CONTACT PLATING	4. INSULATOR COLOR	5. PIN LENGTH
02 TO 40	A. BRASS B. PHOSPHOR BRONZE	T: TIN PLATED S. SELECTIVE G. GOLD FLASH A. 5u" INCH GOLD B. 10u" INCH GOLD C. 15u" INCH GOLD D. 30u" INCH GOLD	1. BLACK	E/F/G

C23- 1 - 2 - 3 - 4 - E / F / G

P1 & P20 = Dip tail ≥ 3mm

P2, P3 ---- P19 = SMT.

UNLESS OTHERWISE SPECIFIED TOLERANCE .X ±0.3 .XX ±0.2 .XXX ±0.1	UNIT: mm	PART NAME: PIN HEADER SINGLE ROW SMT STR 2.54mm	DON CONNEX ELE. CO., LTD
SCALE: / SHEET 1/1		DRAW NO. C23-02CAT-A	
THIRD		FILE NO. C23-02CAT-A	