




XBee DTE 990.006 **Serial Board**



Description

This is a DTE (Data Terminal Equipment) serial module, it means you can connect this device to any DCE (Data Communication Equipment) such as Modems or any DCE device equipped with a female DB9 connector.

Using our 990.002 USB XBee Board on a PC and this module on the device, you can easily transform every serial cable in a wireless connection with a maximum speed of 115K Baud and a distance of up to 1.2Km.

You can use any of the Series1 or Series2 XBee modules and make a reliable and fast serial network in minutes.

Three useful LED's show the TX activity of the Board and the signal strenght (RSSI) the third LED show the associated status. You can change the function of some LED in the XBee EEPROM. The feature connector is useful to program the XBee or for powering external 3.3V devices. You can also use this module as serial level converter for 3.3V TTL signals.

Note

The DB9 Connector is Male type, it is like the serial port conector of computers.

Technical Specifications

3.3V OUT - Output Power:
depends on the Xbee module used.
About 300mA available with XBee,
and 140mA with XBeePRO
modules.

• **Dimensions:** 33 x 48 mm -
max height 13 mm (without XBee)

Features

TX, Associated and RSSI LEDs
to monitor Serial and XBee
activity

Hardware Handshaking full
supported

Energy Saving Mode when the
XBee go in Sleep Mode, the serial
chip do the same


Feature Connector useful for
programming the XBee, powering
the module from a 3.3V source or
power a 3.3V external device. Can
be used as a serial level converter
too.

DROIDS SAS
VIA NANNARELLI 41
00139 ROMA ITALY
www.droids.it
info@droids.it

Back View




Serial Connector




Notes:

.....
.....
.....
.....

Layout



TO SERIAL
DEVICES



Sample application

