


Universal Socket Connectivity Selector Guide

Multi-Tech's universal socket flexible comm-port architecture provides analog dial-up, wireless or Ethernet socket connectivity with interchangeable communications devices. This means you can utilize one system design and populate it with the appropriate connectivity option. Now you can provide a full-line of connectivity by simply dropping in the communications device of choice. In addition, you are assured a seamless migration to future technologies.

(I/O) Tip	1	○		○	64 SPKR (O)
(I/O) Ring	2	○		○	63 GND (O)
Safety Void	3	×		○	62 MICV (I)
(O) TX+	4	○		○	61 VCC (I)
(O) TX-	5	○		○	60 -LED SPD (O)
(I) RX+	6	○		○	59 -LED COL (O)
(I) RX-	7	○		○	58 -LED LINK (O)
Safety Void	8	×		○	57 -LED ACT (O)
	9			○	56 -LED FDX (O)
	10			55	
(O) TXCLK	11	○	Universal Socket	54	
(O) RXCLK	12	○		53	
	13		SocketModem	52	
	14		SocketModem IP	○	51 GPIO (I/O)
	15		SocketModem EDGE	○	50 GPIO (I/O)
	16		SocketModem GPRS	○	49 GPIO (I/O)
	17		SocketModem CDMA	○	48 GPIO (I/O)
	18		SocketWireless Wi-Fi	47	
	19		SocketWireless Bluetooth	46	
	20		SocketEthernet IP	45	
(I)	21			44	
(I) Mic+	22	○		○	43 SPK+ (O)
(I) Mic-	23	○		○	42 SPK- (O)
(I) -Reset	24	○		○	41 GND (I)
(I) USB_VBUS	25	○		○	40 -DTR (I)
(I) GND	26	○		○	39 -DCD (O)
(I/O) USB_DP	27	○		○	38 -CTS (O)
(I/O) USB_DN	28	○		○	37 -DSR (O)
(O) LED DCD	29	○		○	36 -RI (O)
(O) LED RX	30	○		○	35 -TXD (I)
(O) LED DTR	31	○		○	34 -RXD (O)
(O) LED TX	32	○		○	33 -RTS (I)

Our universal socket developer's guide assists you in evaluating the embedded family of connectivity solutions as you consider the different options for current, as well as, future requirements of your product strategy. To obtain a guide, contact Multi-Tech directly or visit our website at www.multitech.com/products/families/socketmodem



SOCKETMODEM® & SOCKETMODEM® IP

The SocketModem embedded modem includes the controller, data pump and data access arrangement (DAA) in one communications device. With connect rates from 300 bps to 56K, it is ideal for applications that periodically need to send or receive data over a standard telephone line. The SocketModem IP embedded modem integrates a complete data/fax modem solution and TCP/IP protocol stack into one communications device.




SOCKETMODEM® EDGE, SOCKETMODEM® GPRS & SOCKETMODEM® CDMA

The SocketModem EDGE, SocketModem GPRS and SocketModem CDMA wireless modems offer standards-based EDGE Class 10, multi-band GSM/GPRS Class 10 and CDMA 2000 1xRTT performance respectively. These quick-to-market communications devices allow developers to add wireless communication to products with a minimum of development time and expense.




SOCKETWIRELESS® Wi-Fi®

The SocketWireless Wi-Fi device server connects serial devices to an IP network via 802.11b wireless networking. It is ideal for remote monitoring, control and configuration of any system.



SOCKETWIRELESS® BLUETOOTH®

The SocketWireless Bluetooth adapter utilizes Bluetooth technology to provide a secure, standards-based wireless connection between a host and a peripheral device. Providing wireless data transfer up to 100 meters, it completely eliminates the need for serial cable connections.



SOCKETETHERNET IP®

The SocketEthernet IP device server connects serial devices to an IP network. It is ideal for remote monitoring, control, maintenance, and configuration of any system.

SocketModem®

Complete, ready-to-integrate voice/data/fax modems.

Models	MT2492SMI-xx	MT2456SMI-xx	MT5600SMI-xx	MT9234SMI-xx	MT5656SMI-xx
Telecom Approvals					
Global		X	X	X	X
Interface					
Serial	X	X	X	X	X
Parallel			X	X	X
Power					
3.3 Volt	X	X	X	X	X
5 Volt	X	X	X	X	X
Maximum Data Rate					
V.92/56K	X		X	X	X
V.34/33.6K	X		X	X	X
V.32bis/14.4K			X		X
V.22bis/2400 baud	X	X			
Fax Capability					
V.34 Fax				X	
V.17 Fax			X	X	X
V.29/V.27/V.21 Fax			X	X	X
Fax Class 1			X	X	X
Fax Class 1.0			X	X	X
Fax Class 2				X	X
Fax Class 2.0/2.1				X	
Fax Compression (MH, MR, MMR)				X	
Error Correction Mode (ECM)				X	
Memory Type					
Flash + RAM				X	
Masked ROM	X	X	X		X
Features					
11-bit Mode			X	X	X
U.S. Caller ID	X	X		X	X
Leased Line				X	
V.22bis Fast Connect	X	X	X	X	X
FastPOS (V.29)			X		X
Callback Security				X	
Industrial Temp Range				X	
Medical Isolation				X	
LED Pin Outputs		X	X	X	X
Extension Pickup Detection	X	X	X		X
Remote Hang-up Detection	X	X	X		X
Line-in-use Detection	X	X	X		X
Digital PBX Detection & Protection	X	X	X		X
Voice Record & Playback (TAM)			X	X	X
Speakerphone I/O					X

See datasheets for more specifications and ordering part numbers.

Developer's guides are available upon request.

Features and specifications are subject to change without notice.

Trademarks / Registered Trademarks: SocketModem, SocketWireless, SocketEthernet IP, Multi-Tech, and the Multi-Tech logo: Multi-Tech Systems, Inc. / Bluetooth is a registered trademark of the Bluetooth SIG, Inc. / Wi-Fi is a registered trademark of the Wi-Fi Alliance. / All other products and technologies are the trademarks or registered trademarks of their respective holders.

World Headquarters

Tel: (763) 785-3500
(800) 328-9717
www.multitech.com

EMEA Headquarters

Multi-Tech Systems (EMEA)
United Kingdom
Tel: +(44) 118 959 7774

Multi-Tech Systems (EMEA)
France
Tel: +(33) 1 49 19 22 06

SocketModem® CDMA, SocketModem® GPRS & SocketModem® EDGE

Complete, ready-to-integrate CDMA, GPRS and EDGE wireless modems.

Models	MTSMC-C	MTSMC-G	MTSMC-E
Network Type	CDMA2000 1XRTT	GPRS Class 10	EDGE Class 10
Dual Band CDMA	X		
Dual Band GSM		X	
Quad-band GSM			X
Short Message Service	X	X	X
14.4K Circuit Switched Data	X	X	X
Maximum Packet Data Rate	153.6K	85.6K	240K
Maximum DTE Speed	230K	115.2K	460K
Class 2.0 Group 3 Fax	X		
GSM Class 1 & 2 Group 3 Fax		X	
Class 1 Group 3 Fax			X
AT Command Compatible	X	X	X
MMCX Antenna Connector	X	X	X
5 VDC Operation	X	X	X

Embedded TCP/IP Networking

Models	MT5656SMI-IP-xx	MT100SEM	MT800SWM	MTSMC-C	MTSMC-G	MTSMC-E
Network Protocol Support						
ARP		X	X		X	
DHCP Client		X	X			
DNS	X	X	X	X	X	X
FTP Client	X	X	X		X	X
ICMP (Ping)	X	X	X			X
IP	X	X	X	X	X	
IPCP	X			X	X	
LCP	X			X		
POP 3 (Receive mail)	X	X	X		X	X
PPP (Dial-out)	X			X	X	
SMTP (Send mail)	X	X	X		X	X
SNTP Client			X			
TCP Socket	X	X	X	X	X	X
Telnet Client					X	
Telnet Server	X	X			X	
UDP Socket	X	X	X	X	X	X
Authentication Protocols						
CHAP	X			X	X	
PAP	X			X	X	