

DEVICELINX™ EMBEDDED NETWORKING MODULES

lantronix.com

LANTRONIX®



Features	XPort	XPort AR	XPort Direct+	MatchPort b/g	MatchPort b/g Pro	MatchPort AR	WiPort b/g	WiPort NR
Operating system	CoBos	Evolution OS™	CoBos	CoBos	Evolution OS	Evolution OS	CoBos	CoBos
10/100 Ethernet (*external RJ45 jack)	•	•	•	•*	•*	•*	•*	•*
Wireless 802.11 b/g				•	•		•	
LAN ↔ 802.11 bridging				•	•		•	
TCP / UDP client-server	•	•	•	•	•	•	•	•
Telnet	•	•	•	•	•	•	•	•
DHCP, BOOTP & AUTOIP	•	•	•	•	•	•	•	•
TFTP	•	•	•	•	•	•	•	•
FTP								
PPP (*Custom)	•*	•*	•*	•*		•	•*	•*
SNMP	•	•	•	•	•	•	•	•
Web server - HTTP	•	•	•	•	•	•	•	•
Web server - CGI (*Custom)	•*	•	•*	•*	•	•	•*	•*
Web server - AJAX		•			•	•		
SSL Secure web server		•			•	•		
SSL Secure data tunneling		•			•	•		
SSH client & server		•			•	•		
Enterprise-grade security & authentication protocols for WLAN					•			
Java support	•	•	•	•	•	•	•	•
AES Encryption (*Option)	•*	•	•	•	•	•	•*	•
Max Configurable GPIO pins (*RTS/CTS on configurable pins)	3*	13*	3	8	7	7	11	11
Software Development Kit (*CPK)	•*	•*	•*	•*	•	•	•*	•*
Flash/RAM	512KB/256KB	4MB/1.25MB	512KB/256KB	2MB/256KB	8MB/8MB	4MB/8MB	2MB/256KB	2MB/256KB
Maximum serial data rate	921 Kbps	230 Kbps	921 Kbps	921 Kbps	230 Kbps	230 Kbps	921 Kbps	921 Kbps
Web manager	•	•	•	•	•	•	•	•
Email client (*Subject Line Only)	•*	•	•*	•*	•	•	•*	•*
Operating Temperature (C°/F°)	-40° to 85°C or 0° to 70°C -40° to 185°F or 32° to 158°F	-40° to 85°C -40° to 185°F	-40° to 85°C -40° to 185°F	-40° to 70°C -40° to 158°F	-40° to 70°C -40° to 158°F	-40° to 70°C -40° to 158°F	-40° to 70°C -40° to 158°F	-40° to 85°C -40° to 185°F
Dimensions (mm)	33.9 x 16.25 x 13.5	45.7 x 16.51 x 17.8	44.3 x 31.75 x 11.76	44.4 x 44.4 x 10.4	44.4 x 44.4 x 10.4	44.4 x 44.4 x 10.4	33.9 x 32.5 x 10.5	33.9 x 32.5 x 10
Serial Interface/# of Ports (*5V Tolerance)	CMOS 3.3V*/1	CMOS 3.3V*/1	CMOS 3.3V*/1	CMOS 3.3V*/2	CMOS 3.3V/2	CMOS 3.3V/2	CMOS 3.3V*/2	CMOS 3.3V*/2
Power Over Ethernet (Pass through)			•	•	•	•	•	•
SmartRoam™				•	•			